

1000 BAR - ROTATIVE NOZZLES



They are an efficient option to clean the internal walls of hard incrustations in pipes, heat exchangers of chemical, petrochemical industries...

Max. pressure of work: 1000 bar.

Replaceable ceramic graft nozzles for longer use.

Type	Inclination jets
KBR	2 Jets to 90° + 2 jets to 45° backwards
KBRV	2 Jets to 90° + 2 jets to 45° to the front
HRH	4 Jets to 45° backwards
HRV	4 Jets to 45° to the front
RGS	4 Jets to 90° ó 75 backwards

Form	Type	Ø (mm)	Length (mm)	Weight (Kg)	Thread connection	Pipe diameter Ø (mm)	Min. Flow at 850 bar (l/m)
05.011 A	KBR	11	30	0,015	M7	12-18	45
05.011 AV	KBRV	11	30	0,015	M7	12-18	45
05.011 B	KBR	11	30	0,015	M8	12-18	45
05.011 BV	KBRV	11	30	0,015	M8	12-18	45
05.012	KBR	11	30	0,015	1/8"	12-18	45
05.012 V	KBRV	11	30	0,015	1/8"	12-18	45
05.016	KBR	16	41	0,040	1/8"	17-30	45
05.016 V	KBRV	16	41	0,040	1/8"	17-30	45
05.0281	RGR	28	62	0,200	1/4"	30-42	30
05.0282	HRH	28	62	0,200	1/4"	30-42	30
05.0283	HRV	28	62	0,200	1/4"	30-42	30
05.0284	KBR	28	62	0,200	1/4"	30-42	30
05.0285	KBRV	28	62	0,200	1/4"	30-42	30
05.0401	RGS	40	85	0,700	M24x1,5	42-55	30
05.0402	HRH	40	85	0,700	M24x1,5	42-55	30
05.0403	HRV	40	85	0,700	M24x1,5	42-55	30
05.0404	KBR	40	85	0,700	M24x1,5	42-55	30
05.0405	KBRV	40	85	0,700	M24x1,5	42-55	30
05.0501	RGR	50	103	1,250	M24x1,5	55-77	30
05.0502	HRH	50	103	1,250	M24x1,5	55-77	30
05.0503	HRV	50	103	1,250	M24x1,5	55-77	30
05.0504	KBR	50	103	1,250	M24x1,5	55-77	30
05.0505	KBRV	50	103	1,250	M24x1,5	55-77	30