

# LANCE NOZZLES PIPE AND HEAT EXCHANGER CLEANING



Form	Thread	Diameter (mm)	Length (mm)	Weight (gr)	Key length (mm)	Max. Pressure (bar)
51	1/4" F	18	38	40	16	500
50	1/8" F	13	30	15	12	
42	M8x1 F	10	30	10	9	
570	1/4" F	18	36	35	-	
572	1/4" F	18	40	40	-	
560	1/8" F	13	36	18	-	
562	1/8" F	13	41	20	-	
59	M6x1 M	8	28	5	-	



Form	Thread	Diameter (mm)	Length (mm)	Weight (gr)	Key measure (mm)	Max. Pressure (bar)
515	1/4" F	Ø18	40	54	16	1.000
505	1/8" F	Ø13	29	21	12	
425	M7x1 F, M8x1 F	Ø10	28,5	11	9	

- The indicated thread in inches is the BSPP type, (Cylindrical thread).
- Material: Stainless steel with thermal treatment of high wear resistance.
- Stock available in a large number of different types in every form, with or without front jets and a large quantity of jets at different angles.
- When ordering please indicate pressure, flow, hose diameter and length.

**ATTENTION:** To use rigid lances. Be careful with the reaction force that the operator has to bear.