

LR ROTARY PORTABLE LANCE

LR-1000 / LR-1400




LR-2800



- The use of this apparatus in heat exchangers multiplies the power of the rotating lance cleaning in comparison with use the fixed lance.
- A pneumatic pistol of slow rotation rotates a high pressure joint, where a lance is fixed. Opening or closing the air passage can adjust rotation speed, even until stopping the lance.
- Using CD type nozzles, the water pressure turning jets impact all the internal periphery of the pipe, a central hard metal blade adds more cutting power.
This type of nozzle is recommended with 2 forward jets at different angles and 2 backward minimizing the reaction force supported by the operator. This also helps to get the waste quickly out making it more productive. It prevents possible accidents that can be produced by pressure accumulation.

Model	LR-1000	LR-1400	LR-2800
Maximum pressure	1.000 bar	1.400 bar	2.800 bar
Maximum flow	76 l/min	76 l/min	38 l/min
Rotation speed	400 rpm	400 rpm	400 rpm
Air supply	51 m ³ /hr / 5,5 bar	51 m ³ /hr / 5,5 bar	51 m ³ /hr / 5,5 bar
Inlet connection	3/8 NPT	9/16 MP	9/16 HP
Weight	5,4 Kg	5,9 Kg	5,9 Kg

CD Type nozzles



Overall diameter

Pressure

Thread

Ø12

1.400 bar

1/8" NPT

Ø16

1.400 bar

1/4" NPT

