

ULTRA HIGH PRESSURE HOSES

- Interior: POM o PA 11/12
- Reinforcement: High resistance steel layers.

- Exterior: PA 11/12.
- Temperature scale: -30° C a +60° C.

TYPE	Ø		Ø Outer sleeve	Working pressure	Burst pressure	Min. Bend radius	Weight
	Inner	Outer					
	mm	mm					

TYPE 2

32	3,0	7,0	9,1	1.100	2.750	60	0,072
42	4,0	8,0	10,0	1.200	3.000	75	0,110
52	5,0	9,4	12,0	1.000	2.500	95	0,125
62	6,3	11,5	13,5	1.100	2.750	110	0,200
82	8,1	13,3	16,1	900	2.250	120	0,250



TYPE 4

34	3,0	8,0	9,8	2.000	5.000	100	0,12
44	4,0	9,9	12,8	2.200	4.500	100	0,14
54	5,0	11,5	15,3	1.800	4.500	130	0,28
64	6,3	12,5	17,0	1.640	4.100	155	0,33
84	8,0	15,1	21,0	1.500	3.800	175	0,44
104	9,7	19,4	26,0	1.400	3.500	190	0,73
134	12,8	22,5	30,0	1.300	3.250	200	0,94
204	19,6	30,0	38,0	1.000	2.500	250	1,39



TYPE 4H

134H	12,8	25,0	30,0	1.400	3.500	110	1,190
------	------	------	------	-------	-------	-----	-------



TYPE 6

46	4,0	12,0	15,6	2.800	7.000	140	0,29
56	4,8	13,2	18,3	2.800	7.000	200	0,47
86	8,0	16,9	22,0	2.100	5.250	225	0,68
136	12,8	24,5	34,0	1.800	4.500	450	1,36
206	19,6	40,0	40,6	1.400	3.500	350	2,10



TYPE 6H

56H	4,8	13,2	18,6	2.800	7.000	200	0,470
86H	7,8	17,2	22,8	2.500	6.250	200	0,830
136H	12,7	27,0	31,9	2.000	5.000	300	1,850



TYPE 8

58	4,6	15,0	18,8	4.000	8.000	200	0,660
88	7,8	19,5	24,0	3.000	7.000	250	1,100
128	12,7	29,8	34,2	2.500	6.250	350	2,500



TYPE 8H

88H	7,8	19,6	24,0	3.200	8.000	280	1,100
138H	13,0	29,9	34,2	3.000	6.250	350	2,500

